

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 16.02.2024

Version number 1

Revision: 16.02.2024

* **SECTION 1: Identification of the substance/mixture and of the company/undertaking**

· **1.1 Product identifier**

· **Trade name:** Aerosol 2K Klarlack

· **(Article number) product ID.:** REZ59

· **1.2 Relevant identified uses of the substance or mixture and uses advised against**

· **Sector of Use**

SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

· **Application of the substance / the mixture:**

painting

FOR PROFESSIONAL USE ONLY

· **Uses advised against** Consumer uses: Private households / general public / consumers

· **1.3 Details of the supplier of the safety data sheet**

· **Manufacturer/Supplier:**

Peter Kwasny GmbH

Heilbronner Str. 96

D-74831 Gundelsheim

Tel.: 0049-(0)6269-95-20

e-mail: labor@kwasny.de

Importer:

<

>

<

>

· **Further information obtainable from:** Product safety department

· **1.4 Emergency telephone number:** Tel.: +49 6269 95 20

· **national:**

National Poisons Information Service, Birmingham

Tel.: 844 892 0111

· **K-Nr. 0053**

* **SECTION 2: Hazards identification**

· **2.1 Classification of the substance or mixture**

· **Classification according to Regulation (EC) No 1272/2008**



flame

Aerosol 1 H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.



Acute Tox. 4 H332 Harmful if inhaled.

Eye Irrit. 2 H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

(Contd. on page 2)

GB

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 16.02.2024

Version number 1

Revision: 16.02.2024

Trade name: Aerosol 2K Klarlack

(Contd. of page 1)

STOT SE 3 H336 May cause drowsiness or dizziness.

2.2 Label elements**Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the GB CLP regulation.

Hazard pictograms

GHS02 GHS07

Signal word Danger**Hazard-determining components of labelling:**Aliphatic polyisocyanate (HDI oligomers, isocyanurate)
acetone

xylene, mixture of isomers

n-butyl acetate

Mixture of alpha-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-omega-hydroxypoly(oxyethylene) and alpha-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-omega-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene)

Hazard statements

H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

H332 Harmful if inhaled.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H336 May cause drowsiness or dizziness.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P271 Use only outdoors or in a well-ventilated area.

P302+P352 IF ON SKIN: Wash with plenty of water.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P312 Call a POISON CENTER/doctor if you feel unwell.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P337+P313 If eye irritation persists: Get medical advice/attention.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Additional information:

Without adequate ventilation, explosive atmosphere/gas mix may be created.

Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

6.2 % of the mixture consists of component(s) of unknown toxicity.

EUH204 Contains isocyanates. May produce an allergic reaction.

Information concerning particular hazards for human and environment: 1272/2008/EC, II, 3.2**2.3 Other hazards****Results of PBT and vPvB assessment**

PBT: Not applicable.

vPvB: Not applicable.

GB

(Contd. on page 3)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 16.02.2024

Version number 1

Revision: 16.02.2024

Trade name: Aerosol 2K Klarlack

(Contd. of page 2)

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Description: Mixture of substances listed below with nonhazardous additions.

Dangerous components:

CAS: 115-10-6 EINECS: 204-065-8 Reg.nr.: 01-2119472128-37-xxxx	dimethyl ether  Flam. Gas 1A, H220; Press. Gas (Comp.), H280, EUH018	25-<50%
CAS: 67-64-1 EINECS: 200-662-2 Reg.nr.: 01-2119471330-49-xxxx	acetone  Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336, EUH066	10-<25%
CAS: 123-86-4 EINECS: 204-658-1 Reg.nr.: 01-2119485493-29-xxxx	n-butyl acetate  Flam. Liq. 3, H226; STOT SE 3, H336, EUH066	10-<25%
CAS: 28182-81-2 NLP: 500-060-2 Reg.nr.: 01-2119485796-17-xxxx	Aliphatic polyisocyanate (HDI oligomers, isocyanurate)  Acute Tox. 4, H332; Skin Sens. 1, H317; STOT SE 3, H335, EUH204	5-<10%
CAS: 1330-20-7 EINECS: 215-535-7 Reg.nr.: 01-2119488216-32-xxxx	xylene, mixture of isomers  Flam. Liq. 3, H226; Asp. Tox. 1, H304; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	2.5-<5%
CAS: 64742-95-6 Reg.nr.: 01-2119455851-35-xxxx	Solvent naphtha (petroleum), light arom. Benzene < 0,1 %  Flam. Liq. 3, H226; Asp. Tox. 1, H304; STOT SE 3, H335; STOT SE 3, H336	1-<2.5%
CAS: 108-65-6 EINECS: 203-603-9 Reg.nr.: 01-2119475791-29-xxxx	2-methoxy-1-methylethyl acetate  Flam. Liq. 3, H226; STOT SE 3, H336	1-<2.5%
CAS: 112-07-2 EINECS: 203-933-3 Reg.nr.: 01-2119475112-47-xxxx	2-butoxyethyl acetate  Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332	1-<2.5%
CAS: 100-41-4 EINECS: 202-849-4 Reg.nr.: 01-2119489370-35-xxxx	ethylbenzene  Flam. Liq. 2, H225; STOT RE 2, H373; Asp. Tox. 1, H304; Acute Tox. 4, H332; Aquatic Chronic 3, H412	<1%
ELINCS: 400-830-7 Reg.nr.: 01-0000015075-76-xxxx	Mixture of alpha-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl) and alpha-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-omega-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene)  Aquatic Chronic 2, H411; Skin Sens. 1, H317	≥ 0.1 -<0.25%
CAS: 80-62-6 EINECS: 201-297-1 Reg.nr.: 01-2119452498-28-xxxx	methyl methacrylate  Flam. Liq. 2, H225; Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335	<0.1%

Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information:

Immediately remove any clothing soiled by the product.

(Contd. on page 4)

GB

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 16.02.2024

Version number 1

Revision: 16.02.2024

Trade name: Aerosol 2K Klarlack

(Contd. of page 3)

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

· After skin contact: Immediately wash with water and soap and rinse thoroughly.

· After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· After swallowing: If symptoms persist consult doctor.

· 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.

· 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

*

SECTION 5: Firefighting measures

· 5.1 Extinguishing media -

· Suitable extinguishing agents: Cool container with water

· 5.2 Special hazards arising from the substance or mixture No further relevant information available.

· 5.3 Advice for firefighters

· Protective equipment: Mouth respiratory protective device.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

· 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Keep away from heat and direct sunlight.

Ensure good ventilation/exhaustion at the workplace.

· Information about fire - and explosion protection:

Do not spray onto a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

· 7.2 Conditions for safe storage, including any incompatibilities

· Storage:

· Requirements to be met by storerooms and receptacles:

Observe official regulations on storing packagings with pressurised containers.

· Information about storage in one common storage facility: Not required.

· Further information about storage conditions: None.

(Contd. on page 5)

GB

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 16.02.2024

Version number 1

Revision: 16.02.2024

Trade name: Aerosol 2K Klarlack

- 7.3 Specific end use(s) No further relevant information available.

(Contd. of page 4)

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

115-10-6 dimethyl ether

WEL	Short-term value: 958 mg/m ³ , 500 ppm Long-term value: 766 mg/m ³ , 400 ppm
-----	---

67-64-1 acetone

WEL	Short-term value: 3620 mg/m ³ , 1500 ppm Long-term value: 1210 mg/m ³ , 500 ppm
-----	--

123-86-4 n-butyl acetate

WEL	Short-term value: 966 mg/m ³ , 200 ppm Long-term value: 724 mg/m ³ , 150 ppm
-----	---

1330-20-7 xylene, mixture of isomers

WEL	Short-term value: 441 mg/m ³ , 100 ppm Long-term value: 220 mg/m ³ , 50 ppm Sk: BMGV
-----	--

108-65-6 2-methoxy-1-methylethyl acetate

WEL	Short-term value: 548 mg/m ³ , 100 ppm Long-term value: 274 mg/m ³ , 50 ppm Sk
-----	--

112-07-2 2-butoxyethyl acetate

WEL	Short-term value: 332 mg/m ³ , 50 ppm Long-term value: 133 mg/m ³ , 20 ppm Sk
-----	---

100-41-4 ethylbenzene

WEL	Short-term value: 552 mg/m ³ , 125 ppm Long-term value: 441 mg/m ³ , 100 ppm Sk
-----	---

80-62-6 methyl methacrylate

WEL	Short-term value: 416 mg/m ³ , 100 ppm Long-term value: 208 mg/m ³ , 50 ppm
-----	--

· Ingredients with biological limit values:

1330-20-7 xylene, mixture of isomers

BMGV	650 mmol/mol creatinine Medium: urine Sampling time: post shift Parameter: methyl hippuric acid
------	--

· Additional information: The lists valid during the making were used as basis.

· 8.2 Exposure controls

· Appropriate engineering controls No further data; see section 7.

· Individual protection measures, such as personal protective equipment

· General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

(Contd. on page 6)

GB

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 16.02.2024

Version number 1

Revision: 16.02.2024

Trade name: Aerosol 2K Klarlack

(Contd. of page 5)

Avoid contact with the eyes and skin.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.



When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Half mask with combination filter, class A1P2 minimum, or breathing mask with outer air supply.

· Hand protection

Protective gloves



The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Penetration time of glove material

Gloves must be changed after every contamination.

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:

butyl rubber, 0,7mm

· Eye/face protection

Safety glasses



Tightly sealed goggles

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Physical state

Aerosol

· Colour:

According to product specification

· Odour:

Characteristic

· Odour threshold:

Not determined.

· Melting point/freezing point:

Undetermined.

· Boiling point or initial boiling point and boiling range

-24.9 °C

· Flammability

Not applicable.

· Lower and upper explosion limit

1.2 Vol % (123-86-4 n-butyl acetate)

· Lower:

18.6 Vol % (115-10-6 dimethyl ether)

· Upper:

<0 °C

· Flash point:

235 °C (115-10-6 dimethyl ether)

· Auto-ignition temperature:

Not determined.

· Decomposition temperature:

Not determined.

· pH

Not determined.

· Viscosity:

Not determined.

· Kinematic viscosity

Not determined.

· Dynamic:

(Contd. on page 7)

GB

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 16.02.2024

Version number 1

Revision: 16.02.2024

Trade name: Aerosol 2K Klarlack

(Contd. of page 6)

· Solubility	
· water:	Not miscible or difficult to mix.
· Partition coefficient n-octanol/water (log value)	Not determined.
· Vapour pressure at 20 °C:	3,400 hPa (115-10-6 dimethyl ether)
· Density and/or relative density	
· Relative density	0.8375 g/ml
· Vapour density	Not determined.
 · 9.2 Other information	
· Appearance:	
· Form:	Aerosol
· Important information on protection of health and environment, and on safety.	
· Ignition temperature:	Product is not selfigniting.
· Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible. Not determined.
· Solvent content:	
· Organic solvents:	80.6 % With propellant gas. Content given by weight.
· VOC (EU)	(<840g/l) 80.52 %
· Solids content:	19.4 %
· Change in condition	
· Evaporation rate	Not applicable.
 · Information with regard to physical hazard classes	
· Explosives	Void
· Flammable gases	Void
· Aerosols	Extremely flammable aerosol. Pressurised container: May burst if heated.
· Oxidising gases	Void
· Gases under pressure	Void
· Flammable liquids	Void
· Flammable solids	Void
· Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void
· Pyrophoric solids	Void
· Self-heating substances and mixtures	Void
· Substances and mixtures, which emit flammable gases in contact with water	Void
· Oxidising liquids	Void
· Oxidising solids	Void
· Organic peroxides	Void
· Corrosive to metals	Void
· Desensitised explosives	Void

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.

(Contd. on page 8)

GB

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 16.02.2024

Version number 1

Revision: 16.02.2024

Trade name: Aerosol 2K Klarlack

- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

(Contd. of page 7)

*** SECTION 11: Toxicological information**

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Harmful if inhaled.

- **LD/LC50 values relevant for classification:**

ATE (Acute Toxicity Estimates)

Dermal	LD50	43,775 mg/kg (rabbit)
Inhalative	LC50/4 h	15.2 mg/l

- **Serious eye damage/irritation** Causes serious eye irritation.
- **Respiratory or skin sensitisation** May cause an allergic skin reaction.
- **STOT-single exposure** May cause drowsiness or dizziness.

- **11.2 Information on other hazards**

- **Endocrine disrupting properties**

None of the ingredients is listed.

*** SECTION 12: Ecological information**

- **12.1 Toxicity**

- **Aquatic toxicity:** No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.

- **12.5 Results of PBT and vPvB assessment**

- **PBT:** Not applicable.

- **vPvB:** Ikke relevant.

- **12.6 Endocrine disrupting properties**

The product does not contain substances with endocrine disrupting properties.

- **12.7 Other adverse effects**

- **Additional ecological information:**

- **General notes:**

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

*** SECTION 13: Disposal considerations**

- **13.1 Waste treatment methods**

- **Recommendation**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- **Uncleaned packaging:**

· **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information

- **14.1 UN number or ID number**

· **ADR, IMDG, IATA**

UN1950

(Contd. on page 9)

GB

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 16.02.2024

Version number 1

Revision: 16.02.2024

Trade name: Aerosol 2K Klarlack

(Contd. of page 8)

<ul style="list-style-type: none"> · 14.2 UN proper shipping name · ADR 1950 AEROSOLS · IMDG AEROSOLS · IATA AEROSOLS, flammable 	
<ul style="list-style-type: none"> · 14.3 Transport hazard class(es) · ADR 	
	<ul style="list-style-type: none"> · Class 2 5F Gases. · Label 2.1
<ul style="list-style-type: none"> · IMDG, IATA 	
	<ul style="list-style-type: none"> · Class 2.1 Gases. · Label 2.1
<ul style="list-style-type: none"> · 14.4 Packing group · ADR, IMDG, IATA 	
<ul style="list-style-type: none"> · 14.5 Environmental hazards: · Marine pollutant: 	
<ul style="list-style-type: none"> · 14.6 Special precautions for user · Hazard identification number (Kemler code): 	
<ul style="list-style-type: none"> · EMS Number: · Stowage Code 	
<ul style="list-style-type: none"> · Segregation Code 	
<ul style="list-style-type: none"> · 14.7 Maritime transport in bulk according to IMO instruments 	
<ul style="list-style-type: none"> · Transport/Additional information: 	
<ul style="list-style-type: none"> · ADR · Limited quantities (LQ) · Excepted quantities (EQ) 	
<ul style="list-style-type: none"> · Transport category 	

(Contd. on page 10)

GB

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 16.02.2024

Version number 1

Revision: 16.02.2024

Trade name: Aerosol 2K Klarlack

(Contd. of page 9)

· Tunnel restriction code	D
· IMDG	
· Limited quantities (LQ)	IL
· Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity
· UN "Model Regulation":	UN 1950 AEROSOLS, 2.1

* **SECTION 15: Regulatory information**

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture	
VOC: <840g/l	
· Poisons Act	
· Regulated explosives precursors	
None of the ingredients is listed.	
· Regulated poisons	
None of the ingredients is listed.	
· Reportable explosives precursors	
67-64-1 acetone	Listed
· Reportable poisons	
None of the ingredients is listed.	
· Directive 2012/18/EU	
· Named dangerous substances - ANNEX I None of the ingredients is listed.	
· Seveso category P3a FLAMMABLE AEROSOLS	
· Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t	
· Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t	
· National regulations:	
· Technical instructions (air):	
Class Share in %	
NK 50-100	
· Waterhazard class: Water hazard class 2 (Self-assessment): hazardous for water.	
· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.	

* **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases
H220 Extremely flammable gas.
H225 Highly flammable liquid and vapour.
H226 Flammable liquid and vapour.
H280 Contains gas under pressure; may explode if heated.
H302 Harmful if swallowed.
H304 May be fatal if swallowed and enters airways.
H312 Harmful in contact with skin.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.

(Contd. on page 11)

GB

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 16.02.2024

Version number 1

Revision: 16.02.2024

Trade name: Aerosol 2K Klarlack

(Contd. of page 10)

H332 *Harmful if inhaled.*
 H335 *May cause respiratory irritation.*
 H336 *May cause drowsiness or dizziness.*
 H373 *May cause damage to organs through prolonged or repeated exposure.*
 H411 *Toxic to aquatic life with long lasting effects.*
 H412 *Harmful to aquatic life with long lasting effects.*
 EUH018 *In use may form flammable/explosive vapour-air mixture.*
 EUH066 *Repeated exposure may cause skin dryness or cracking.*
 EUH204 *Contains isocyanates. May produce an allergic reaction.*

· Department issuing SDS: Product safety department

· Abbreviations and acronyms:

ADR: *Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)*
 IMDG: *International Maritime Code for Dangerous Goods*
 IATA: *International Air Transport Association*
 GHS: *Globally Harmonised System of Classification and Labelling of Chemicals*
 EINECS: *European Inventory of Existing Commercial Chemical Substances*
 ELINCS: *European List of Notified Chemical Substances*
 CAS: *Chemical Abstracts Service (division of the American Chemical Society)*
 LC50: *Lethal concentration, 50 percent*
 LD50: *Lethal dose, 50 percent*
 PBT: *Persistent, Bioaccumulative and Toxic*
 vPvB: *very Persistent and very Bioaccumulative*
 ATE: *Acute toxicity estimate values*
 Flam. Gas 1A: *Flammable gases – Category 1A*
 Aerosol 1: *Aerosols – Category 1*
 : *Aerosols – Category 3*
 Press. Gas (Comp.): *Gases under pressure – Compressed gas*
 Flam. Liq. 2: *Flammable liquids – Category 2*
 Flam. Liq. 3: *Flammable liquids – Category 3*
 Acute Tox. 4: *Acute toxicity – Category 4*
 Skin Irrit. 2: *Skin corrosion/irritation – Category 2*
 Eye Irrit. 2: *Serious eye damage/eye irritation – Category 2*
 Skin Sens. 1: *Skin sensitisation – Category 1*
 STOT SE 3: *Specific target organ toxicity (single exposure) – Category 3*
 STOT RE 2: *Specific target organ toxicity (repeated exposure) – Category 2*
 Asp. Tox. 1: *Aspiration hazard – Category 1*
 Aquatic Chronic 2: *Hazardous to the aquatic environment - long-term aquatic hazard – Category 2*
 Aquatic Chronic 3: *Hazardous to the aquatic environment - long-term aquatic hazard – Category 3*

· * Data compared to the previous version altered.

GB